

proxSafe®

Key Management & Smart Storage Systems

The intelligent management system for keys and equipment with comprehensive audit and reporting capabilities. Control who can have access to individual items and restrict when they can be taken. Keys, radios, test equipment, tools, laptops and much more can now be managed efficiently with increased accountability so you know where they are and who has them. The powerful software Commander Connect allows easy configuration and control of access rights, time profiles and the creation of individual reports. That way you stay in control at all times and make the best use of your equipment.



Modular key cabinet with up to 32 slots

The proxSafe smart II 3 U is the perfect choice to keep a small number of keys safe and to issue them exclusively to authorised people. Users and keyTags are identified contactlessly; all procedures are logged automatically.

It is possible to operate the proxSafe smart II 3 U in conjunction with different terminals: C1-C4 can be utilised. The system manages up to 32 keys; to connect to a PC it is equipped with a USB port or, optionally, with an Ethernet connection. Each proxSafe housing is equipped with tamper contacts and 4 relays; these are not only designed to signal different alarms via a network but also locally.

The keyPanels are installed at the place of installation with different slot densities. The size of the memory of the operator terminal facilitates seamless operation, even in the event of a network failure. An installed battery provides power in the event of a power failure to ensure the operational availability of the system at all times. In an emergency it is possible to unlock all of the slots with the aid of a security key.

Key slots and keyTags are designed for robust operations. The use of RFID technology means the keyTags are not affected by soiling, corrosion or wear. proxSafe keyTags and the corresponding slots need no cleaning or maintenance whatsoever.

Your benefits at a glance:

- **Energy-saving mode with back-up battery for very long-term operations**
- **Contactless technology, maintenance-free**
- **Straightforward emergency opening feature**
- **Standalone operation or remote controlled**
- **4 outputs for local alarms**

Technical data

Dimensions WxHxD /

weight: 630 x 299 x 210 mm / 15 kg

Housing material: Sheet steel, powder coated

Sheet steel gauge:

Housing 1.25 mm
Door 2 mm

Colour: Similar to RAL 9006, DB502

Operating temperature: +5...+50°C

Relative humidity:

5...95%, non-condensing

Power requirement: 110...240 VAC

keyTag frequency: 125 kHz

Door options: Metal door, not shown
Metal door with viewing window

Back-up battery: 12 VDC / 2.3 Ah

Isolated contacts:

4x 30 VDC / 1 A
for up to 16 alarms

Available panels:

1x 32 DD:	32 slots
1x 16 SD:	16 slots
1x 16 DD:	16 slots
1x 8 SD:	8 slots